



PRODUCT INFORMATION

Rust+Rescue™ 200

Stellar Solutions, Inc.
4511 Prime Parkway
McHenry, IL 60050
Phone (847) 854-2800
Fax (847) 854-2830
stellar@citrisurf.com
www.citrisurf.com

Technical Data:

Description: *Rust Rescue 200* is a high quality blend of chemicals formulated for the protection of stainless steel and other metal surfaces in conjunction with *CitriSurf* passivation, especially in environments where moisture and harsh atmospheric chemicals are expected to or have lead to corrosion.

Physical Properties:

Chemical Composition	Calcium sulfonate, proprietary ingredients
Operating Temperature	70-90°F
Flash Point	150°F
Normal working concentration	Use as received

Packaging: 1 quart, 1 gallon, 55 gallon metal containers, or 12 oz. trigger sprayer cans.

Application Procedure: Remove any existing rust first with a rust remover such as *CitriSurf 77 Plus* or *CitriSurf 2310*, using the procedure recommended for that product. Then allow surface to dry completely before applying *Rust Rescue*. All equipment, mixers, applicators or pumps should be clean and dry prior to use.

Prior to use, mix thoroughly by shaking or stirring. Apply a light coat of *Rust Rescue 200* to the surface to be protected with a clean soft cloth, sprayer, brush or roller. Coverage is approximately 300 square feet per gallon. Wait approximately 2 to 3 minutes and then wipe off the excess product. Allow the surface to dry completely in air. Drying can be accelerated by use of a hot air oven or other drying medium such as an air blower (hair dryer).

Notes on Use: Although very safe in normal use, *Rust Rescue 200* is a Calcium Sulfonate based material, and as such it may cause irritation to exposed surfaces of the body for some persons. **See Material Safety Data Sheet before using this material.** Rubber or plastic gloves should be worn to apply the product to the surface or to wipe it dry.

Disposal: Dispose of according to all federal, state and local regulations.

page 2...

Storage: *Rust Rescue 200* should be stored at temperatures between 50°F and 120°F in steel or aluminum containers.

Technical Services: For technical assistance, please contact Stellar Solutions at (847) 854-2800.

Testing of your products with *Rust Rescue* before using in production is recommended. Every product and production facility is different, and requires testing to ensure that *Rust Rescue* is compatible with the particular situation. No warranty is implied, or may be given in writing or verbally without the written permission of Stellar Solutions, Inc.

01/2014