



# PENOFIN FOR PRESSURE TREATED

Suitable for all types of pressure-treated wood

PRODUCT DATA SHEET

## PENOFIN FOR PRESSURE TREATED WOOD:

Penofin's Pressure Treated Formula contains sustainably harvested Brazilian Rosewood Oil to give the wood a natural tone and texture. Suitable for all types of pressure treated wood. Pressure Treated Penofin is formulated to restore the beautiful wood tones homeowners want. It comes in three natural tones: Rainier, Yosemite, and Tahoe. It penetrates pressure-treated wood like no other stain. Brazilian Rosewood Oil penetrates and stabilizes the wood fibers for control of carcinogenic releases, as stated by the environmental protection agency. They recommend using a deep, low-solid, penetrating oil finish.

## PERFORMANCE FEATURES

- ◆ Non-Film Forming
- ◆ 99% UV Protection
- ◆ VOC <550, 250, or 100 g/l based on local regulations
- ◆ VOC Compliant nation wide
- ◆ Exterior Use
- ◆ Dries to Touch in 4 hours.
- ◆ Natural Oil Beauty
- ◆ Preserves and Protects
- ◆ Extends life of wood
- ◆ Superior mildew protection

## PRESSURE TREATED APPLICA-

### TIONS

- ◆ Decks
- ◆ Log Homes
- ◆ Siding
- ◆ Furniture
- ◆ Fencing
- ◆ Wood Art
- ◆ Spas
- ◆ Docks
- ◆ Floors
- ◆ Doors
- ◆ Window Trim

## TECHNICAL DATA:

**VOC:** <550, 250, or 100 g/l based on local air quality regulations. Refer to the label on your can.

**Coverage:** 175-300sqft/Gallon

**Installation Temperature:** 45°F-80°F.

**Relative Humidity:** 85% Maximum, below 80% for best results.

**Dry to the Touch:** 3-4 hours

**Serviceable:** 12 hours

**Moisture Resistant:** 24 hours

**Full Cure:** 4-7 days

## SURFACE PREPARATION:

New wood can be dirty from transport & construction, and mill glaze could be present. For prep we recommend the **First Step Prep** to lightly clean the wood and remove the mill glaze from the surface. Old bare wood should be cleaned using the **Pro-Tech Cleaner #2**. If greying or discoloration is present, follow the cleaner with the **Pro-Tech Brightener #3**. If wood has been previously treated with a non-Penofin product, it's recommended to chemically strip the wood with an Acrylic stripper, followed by the **Pro-Tech Cleaner #2** and **Pro-Tech**

## **Brightener #3.**

## APPLICATION:

Stir product thoroughly before and during application. Apply at temperatures between 45°F & 80°F. Penofin is stable under freeze/thaw conditions. For optimum performance bring the stain to room temperature before application. Do not apply if the wood is hot to the touch. Using a brush, stain pad, or plastic pump sprayer apply a liberal coat to the wood. Protect any adjacent areas you do not wish to stain by tarping or masking the area off.

Penofin is a penetrating oil finish and will penetrate any porous surface. All Penofin 20-30 minutes to penetrate into the wood. This step is important as it allows the finish to coat the individual fibers of the wood, protecting your investment from the inside out. After 20-30 minutes wipe the surface thoroughly with clean non-lint cloths to remove any excess finish.

If using the 2 coat (550 VOC formula), wait a minimum of 4 hours before applying a second light coat of Penofin. Again after 20-30 minutes wipe the surface thoroughly to remove any excess finish. Penofin is a penetrating finish and is not a surface coating. Failure to wipe will allow the finish to dry on the surface of the wood and will result in a tacky finish.

**DANGER! THIS PRODUCT MAY CATCH FIRE SPONTANEOUSLY. TO AVOID SPONTANEOUS COMBUSTION, SOAK OILY CLOTHS, RAGS, ETC. IN WATER IN A SEALABLE METAL CONTAINER AWAY FROM BUILDINGS AND OTHER COMBUSTIBLE MATERIALS. DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS. FAILURE TO FOLLOW THESE INSTRUCTIONS WILL RESULT IN A RUNAWAY AND UNCONTROLLABLE TEMPERATURE RISE AND FIRE AND POSSIBLY CAUSE PROPERTY DAMAGE AND PERSONAL INJURY.**

## CLEAN UP:

Paint Thinner or Mineral Spirits

## MAINTENANCE:

Keep the wood clean, free of debris or standing water for long periods of time. Twice yearly, clean the surface with Penofin **Pro-Tech Cleaner Step 2**. Follow with Penofin **Pro-Tech Brightener Step 3**, if wood has grayed or started to darken. Allow the wood to dry and simply coat any areas that might show wear or tear from furniture, weather or foot traffic with another light application of Penofin.

Please visit our website [www.penofin.com](http://www.penofin.com) for more application & wood care tips, or call our live customer service line at:

**1-800-PENOFIN Monday thru Friday 7am to 4pm Pacific Standard Time, or email us at [mail@penofin.com](mailto:mail@penofin.com)**